

V-FIT™ Harness

Technical Data Sheet



CAPACITY	ANSI Z359.11: 130–310 lbs. (59–140 kg) OSHA / CSA Z259.10: 400 lbs. (180 kg)
BRAND	MSA
SUB BRAND / MODEL NAME	V-FIT
SIZES	Extra Small, Standard, Extra Large, Super Extra Large
D-RING LOCATIONS	Dorsal (<i>back</i>), hips (<i>optional</i>), shoulders (<i>optional</i>), chest (<i>optional</i>)
LEG STRAP BUCKLE OPTIONS	Quick connect, tongue buckle
PADDING LOCATIONS	Shoulder, waist (<i>construction</i>), legs (<i>optional</i>)
RFID EQUIPPED	Yes (<i>inside label pack</i>)
THREAD / STITCHING	Polyester
WEB	Polyester, nano-technology treated
WEB KEEPER	Polyester, hook and loop closure
LEG BUCKLES	Anodized forged aluminum, stainless steel tabs and adjuster
CHEST BUCKLE	Anodized forged aluminum, stainless steel tabs and adjuster
D-RING	Anodized forged aluminum
PFL ADAPTER	Integrated polymer dedicated PFL attachment point
PADDING	Breathable spacer mesh and foam
PRODUCT WEIGHT	3.53 lbs. – Standard back D-ring with quick connect leg straps
SHIPPING DIMENSIONS	6" x 25" x 22"
PRODUCT STYLES	Racing style
STANDARDS	ANSI Z359.11, CSA Z259.10, OSHA

Note: This Bulletin contains only a general description of the products shown. While product uses and performance capabilities are generally described, the products shall not, under any circumstances, be used by untrained or unqualified individuals. The products shall not be used until the product instructions/user manual, which contains detailed information concerning the proper use and care of the products, including any warnings or cautions, have been thoroughly read and understood. Specifications are subject to change without prior notice.

MSA operates in over 40 countries worldwide. To find an MSA office near you, please visit [MSAafety.com/offices](https://www.MSAafety.com/offices).