

Product data sheet uvex silv-Air 8313 FFP3 NR D



Product information

Product features	• Particle-filtering flat fold mask with exhalation valve • Protection level FFP 3 • Soft material edges for increased comfort • 4-point headband attachment allows an individual and secure fit • Integrated, flexible, adjustable nose clip • Hydrophobic coating • Soft sealing lip guarantees a secure, comfortable sealed position of the mask • Exhalation valve reduces breathing resistance and build-up of heat and moisture in the mask • The masks are individually packed • Mask fulfils the requirements of the dolomite dust test (D)
Materials	Headband: textile Nose clip: metal, PP Sealing lip: synthetic foam Filter/mask: PP, Polyester Valve: PP
Weight	23 g
Standard	EN 149:2001 + A1:2009

Versions

Article number	Colour/Version	Retail unit
8788313	Flat fold mask FFP3, white with valve	15 pcs. per box

Packaging sizes

Box	approx. 180 x 160 x 160 mm
Outer Carton	approx. 610 x 505 x 340 mm

Maximum breathing resistance acc. to EN149 in mbar

	Inhalation resistance 30l/min.	Inhalation resistance 95l/min.	Exhalation resistance 160l/min.
FFP1	0,6	2,1	3,0
FFP2	0,7	2,4	3,0
FFP3	1,0	3,0	3,0

Areas of use*

The respiratory protection mask can be used against solid, aqueous and non-volatile liquid aerosols up to 30 times the respective limit values.	Woodworking, hard wood, chromium, asbestos (short periods of work), stainless steel, lead, welding, dust that contain beryllium, arsenic, cadmium or cobalt. Medical waste disposal, fungal spores, legionella bacteria, infections, viruses, bacteria, enzyme, nanoparticles.
--	--

*Please note that the above mentioned areas of use are examples only. The selection of PPE needs to be carried out by a competent person, in conjunction with relevant and current legislation.

All respiratory protective devices fall into PPE category III (high risks).

Uvex accepts no liability for any possible harm or damage which may result from this information.
This data sheet does not replace a detailed risk assessment nor seeking specialist advice.

UVEX ARBEITSSCHUTZ GMBH, Würzburger Str. 181-189, D-90766 Fürth