

INTERFACE PLUS**82045-G08-GA330**

Description: Flock lined nitrile gloves, 18 mil.

- Features & Benefits:
- * Nitrile rubber for better chemical resistance
 - * Outstanding abrasion resistance
 - * Anti-slip pattern for good grip in wet and dry conditions
 - * Extra thick for added protection
 - * Straight cuff
 - * Compliant with (EC) No.1935/2004, EU 10/2011 & BFR XXI (Green)
 - * Manufactured under a stringent quality management system

Applications: Aircraft Industry, Automotive Industry, Chemical Industry, Petrochemical Industry

Elastomer: Nitrile rubber

Thickness: 0.45 +/- 0.05 mm

Lining: Flocklined

Former: Reverse Lozenge, CVIL

Exterior: Finished smooth

Cuff Types: Straight

Treatments: Chlorinated

Colours: Blue B14, Green G8

AQL - Critical: 1.5

Major: 4



CE Certification: Conforms to PPE Regulation EU 2016/425 to (Complex Design) Personal Protective Equipment after assessment against standards EN 374-1:2016+A1:2018, EN 388:2016+A1:2018, EN 374-5 : 2016, EN ISO 21420:2020 and ISO 18889:2019

Conforms to:

Physical Dimensions:	Size	Palm	Wrist	Cuff	Length
	7	214	206	296	330
	8	220	218	302	330
	9	244	234	310	330
	10	268	256	326	330
	11	278	268	330	330
		Circumference in mm, +/- 10 mm		Tol. +/- 10 mm	

Shelf Life 5 Years

EN 374-4

Protection against Chemical hazards

Performance

Degradation %

EN ISO 374-1/TYPE A



* Methanol (A)	Level 2	70.1
* Toluene (F)	Level 1	81.8
* n-Heptane (J)	Level 6	0
* Sodium hydroxide 40% (K)	Level 6	4.5
* Sulphuric acid 96% (L)	Level 3	61.9
* Nitric acid 65% (M)	Level 2	98.7
* Acetic acid 99% (N)	Level 3	91.9
* Ammonium hydroxide 25% (O)	Level 6	-5.8
* Hydrogen peroxide 30% (P)	Level 6	-11.7
* Formaldehyde 37% (T)	Level 6	-15.6

Note: Printed copies are valid only on the date printed

Printed Date: 01-Dec-2023

Revision:8

Published Date: 01-Dec-2023



No: 400, Deans Road, Colombo 10, Sri Lanka

Phone: +94-0122-683-964

Fax: +94-0122-699-018

E-Mail: postmast@dplgroup.com

Protection against Mechanical hazards

Performance

EN 388



- * Abrasion resistance
- * Blade cut resistance
- * Tear resistance
- * Puncture resistance
- * TDM cut resistance

Level 4
Level 1
Level 0
Level 1
X

Protection against Micro-organisms risk

Performance

EN ISO 374-5



- * Protection against bacteria and fungi
- * Protection against viruses

Pass
Pass

Protection against liquid pesticides

Performance

ISO 18889:2019



- * G2