

Description: Unlined natural rubber gloves, 43 mil, rolled cuff

- Features & Benefits:
- * Anatomically shaped to provide good fit
 - * Beaded cuff to improve tear resistance during donning and removal and help prevent droplets from travelling beyond the glove length
 - * Easy-on-easy-off
 - * Excellent abrasion resistance
 - * Extra long cuff to protect forearm
 - * Extra thick for added protection
 - * Low in soluble proteins
 - * Manufactured under a stringent quality management system
 - * Natural Rubber, No filter , No flock

Applications: Agriculture, Chemical Industry, Fishing, Animal husbandary

Elastomer: Natural rubber

Thickness: 1.10 +/- 0.10 mm

Lining: Unlined chlorinated

Former: Plain, NIVP

Exterior: Finished smooth

Cuff Types: Bead rolled

Treatments: Chlorinated

Colours:

AQL - Critical: 1.5

Major: 4



CE Certification: Conforms to PPE Regulation EU 2016/425 to (Complex Design) Personal Protective Equipment after assessment against standards EN 374-1:2016+A1:2018, EN 374-5:2016, EN 388:2016+A1:2018, EN ISO 21420:2020, EN 407:2020 and EN 421:2010 (radioactive contamination only)

Conforms to:

Physical Dimensions:	Size	Palm	Wrist	Cuff	Length
	9	234	230	435	600
	10	262	250	449	600
	11	278	269	464	600
				Circumference in mm, +/- 5 mm	Tol. +/- 10 mm

Shelf Life 3 Years

EN 374-4

Protection against Chemical hazards	Performance	Degradation %
EN ISO 374-1/TYP A		
	* Methanol (A)	Level 6 0.4
	* Sodium hydroxide 40% (K)	Level 6 -10.2
	* Sulphuric acid 96% (L)	Level 4 31.4
	* Nitric acid 65% (M)	Level 6 16.2
	* Acetic acid 99% (N)	Level 5 20
	* Ammonium hydroxide 25% (O)	Level 3 -8.1
	* Hydrogen peroxide 30% (P)	Level 6 32.1
	* Formaldehyde 37% (T)	Level 6 -4.4

Note: Printed copies are valid only on the date printed

Printed Date: 28-Nov-2023

Revision:9

Published Date: 28-Nov-2023



No: 400, Deans Road, Colombo 10, Sri Lanka

Phone: +94-0122-683-964

Fax: +94-0122-699-018

E-Mail: postmast@dplgroup.com

Protection against Mechanical hazards

Performance

EN 388



- * Abrasion resistance
- * Blade cut resistance
- * Tear resistance
- * Puncture resistance
- * TDM cut resistance

Level 4
Level 1
Level 2
Level 1
X

Protection against Micro-organisms risk

Performance

EN ISO 374-5



- * Protection against bacteria and fungi
- * Protection against viruses

Pass
n/a

Protection against Thermal risks

Performance

EN 407



- * Contact heat
- * Convective heat
- * Radiant heat
- * Small splashes of molten metal
- * Large quantities of molten metal
- * Limited Flame Spread

Level 1
X
X
X
X
X