



Fall protection

AN203200ZD

ENERGY ABSORBING LANYARDS

Energy absorbing lanyard made of high impact webbing, for short trips



Specific benefits



Hygiene

- Harnesses and textiles can be washed with neutral soap



Performance

- Strap with improved abrasion resistance and certified for use on sharp edges
- Certification above the maximum rated load of 100 kg; product certified at 140 kg

Applications

- Public works
- Finishing works / Craftsmanship
- Automotive
- Storage

Certifications and norms



EN355

HORIZONTAL CERTIFICATION - 140 KG
RFU 11.062
140 KG

Protects against risks



Fall



Fall protection

AN203200ZD

ENERGY ABSORBING LANYARDS

Energy absorbing lanyard made of high impact webbing, for short trips

Standards - Details

Technical details

Type of equipment	Flat webbing lanyard with energy absorber
Composition of the main support	Polyester
Length (m)	2
Gate opening (mm)	55
Opening (inch)	2.1616
Lock	Automatic system
With connector	yes
Fall factor	F2
Color	Orange
Connector (user side)	Automatic lock hook, steel, opening 18mm
Ending	2 sewn thimble loops
Connector (structure side)	1 automatic lock hook, steel, opening 55 mm
Lifespan from manufacturing (years)	10
Weight (kg)	1
Fall arrest work situations	Vertical movement on a permanent structure, Movement on lifeline, Short vertical movement or movement on inclined surface (less than 3 m), Short horizontal movement (less than 3 m)
Lenght (ft)	6.5616



Fall protection

AN203200ZD

ENERGY ABSORBING LANYARDS

Energy absorbing lanyard made of high impact webbing, for short trips

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
ENAS1002DA011 [AN203200ZD]	Orange	2 m	AN203200ZD	3295249264970	13295249264977	5	1	6.146 kg	28.4 cm	43.2 cm	14.6 cm



Multiple sales



Minimum sales



Box Width



Box Depth



Box Height