



Fall protection

AN213150ZDD

ENERGY ABSORBING LANYARDS

Double energy-absorbing lanyard in high-strength webbing for short movements.



Specific benefits



Hygiene

- Harnesses and textiles can be washed with neutral soap



Performance

- Strap with improved abrasion resistance and certified for use on sharp edges
- Certification above the maximum rated load of 100 kg; product certified at 140 kg

Applications

- Public works
- Automotive
- Power Energy
- Storage

Certifications and norms



EN355

HORIZONTAL CERTIFICATION - 140 KG
RFU 11.062
140 KG



Fall protection

AN213150ZDD

ENERGY ABSORBING LANYARDS

Double energy-absorbing lanyard in high-strength webbing for short movements.

Standards - Details

Technical details

Type of equipment	Flat webbing lanyard with energy absorber
Composition of the main support	Steel, Polyester
Length (m)	1,5
Lock	Automatic system
With connector	yes
Color	Orange
Connector (user side)	Automatic lock hook, steel, opening 19mm
Ending	2 sewn thimble loops
Connector (structure side)	2 automatic lock hooks, steel, opening 55 mm
Lifespan from manufacturing (years)	10
Weight (kg)	1,4
Maximum load for one person (kg)	140
Lenght (ft)	4.9213



Fall protection

AN213150ZDD

ENERGY ABSORBING LANYARDS

Double energy-absorbing lanyard in high-strength webbing for short movements.

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
ENAD11Z5DZ01 1 [AN213150ZDD]	Orange	1.50 m	AN213150ZDD	3295249294335	13295249294332	5	1	0.0 kg	20.6 cm	53.5 cm	14.5 cm



Multiple sales



Minimum sales



Box Width



Box Depth



Box Height