



Fall protection

LO147150CDD

LANYARDS

1.5 metre double lanyard with large opening connector, for maximum versatility and connection to any type of structure



Applications

- Building
- Finishing works / Craftsmanship
- Maintenance
- Chemical industry
- Oil & Gas (extraction)
- Mining

Certifications and norms



EN354

Protects against risks



Fall



Fall protection

LO147150CDD

LANYARDS

1.5 metre double lanyard with large opening connector, for maximum versatility and connection to any type of structure

Standards - Details

Technical details

Type of equipment	Braided rope
Composition of the main support	Steel, Polyamide
Length (m)	1,5
Rope diameter (mm)	10,5
With connector	yes
Color	White
Connector (user side)	Screw carabiner, steel, opening 18mm
Ending	1 loop sewn thimble
Connector (structure side)	2 automatic lock hooks, steel, opening 55 mm
Weight (kg)	1,4
Fall arrest work situations	Restraint
Lenght (ft)	4.9213



Fall protection

LO147150CDD

LANYARDS

1.5 metre double lanyard with large opening connector, for maximum versatility and connection to any type of structure

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
LIN01Z51031Z5 [LO147150CDD]	White	1.50 m	LO147150CDD	3660348006361	13660348006368	5	1	7.5 kg	20.6 cm	53.5 cm	14.5 cm



Multiple sales



Minimum sales



Box Width



Box Depth



Box Height