



Fall protection

MAXIBLOC AN10006T

RETRACTABLE FALL ARRESTERS

Lightweight and compact self-retractable cable fall arrester for easy installation and use for distances of up to 6 metres



Specific benefits



Performance

• Certification above the maximum rated load of 100 kg: product certified at 150 kg

Applications

- Building
- Finishing works / Craftsmanship

Certifications and norms



EN360
RFU 11.062
150 KG



UL-AR EN360

AR 1983

Protects against risks



Fall



Fall protection

MAXIBLOC AN10006T

RETRACTABLE FALL ARRESTERS

Lightweight and compact self-retractable cable fall arrester for easy installation and use for distances of up to 6 metres

Standards - Details

Technical details

Type of equipment	Cable reel
Composition of the main support	ABS, Galvanized steel
Max. length (m)	6
ARA lenght (m)	6
ARA lenght (inch)	236.2206
Cable diameter (mm)	4
Included elements	Included energy absorber
Color	Black
Connector (user side)	Small hook, steel, opening 21 mm
Benefits element	Fall indicator
Lifespan from manufacturing (years)	10
Weight (kg)	2,8
Fall arrest work situations	Vertical movement on a permanent structure, Long vertical movement or movement on inclined surface
Use of self retracting	Vertical



Fall protection

MAXIBLOC AN10006T

RETRACTABLE FALL ARRESTERS

Lightweight and compact self-retractable cable fall arrester for easy installation and use for distances of up to 6 metres

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
SRLMAXC00601 BK [AN10006T]	Black	6 m	MAXIBLOC AN10006T	3295249219901	13295249219908	1	1	2.8 kg	30.0 cm	17.0 cm	10.0 cm



Multiple sales



Minimum sales



Box Width



Box Depth



Box Height